



SIM8950 Series SPI Driver Development Guide Manual_V1.00.01

Smart Module

Shanghai SIMCom Wireless Solutions Ltd.
Building A, SIM Technology Building, No.633, Jinzhong Road
Changning District 200335
Tel: 86-21-31575100/31575200
support@simcom.com
www.simcom.com

Document Title:	SIM8950 Series SPI Driver Development Guide Manual
Version:	1.00.01
Date:	2018-11-22
Status:	Release
SIM8950 Series SPI Driver Development Guide Manual_V1.01	SIM8950 Series SPI Driver Development Guide Manual

General Notes

SIMCom offers this information as a service to its customers, to support application and engineering efforts that use the products designed by SIMCom. The information provided is based upon requirements specifically provided to SIMCom by the customers. SIMCom has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by SIMCom within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

Copyright

This document contains proprietary technical information which is the property of SIMCom Limited., copying of this document and giving it to others and the using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. All rights reserved in the event of grant of a patent or the registration of a utility model or design. All specification supplied herein are subject to change without notice at any time.

Copyright © Shanghai SIMCom Wireless Solutions Ltd. 2018

Version History

Version	Date	Chapter	What is new
V1.00	2018-09-12		New version
V1.01	2018-09-19	2.1.1	1. SIM8950 Series SPI Driver Development Guide Manual

Contents

Version History	2
Contents	3
1 Introduction.....	4
1.1 The Inter-Integrated Circuit(I2C) Overview	4
2 SPI Configure Process	4
2.1 Dts Configure	4
2.2 GPIO SPI Configure	5

This document describes the Serial Peripheral Interface (SPI) and explains how to configure it in the kernel .
Through these chapter , you can know to configure SPI.

1 Introduction

1.1 The Inter-Integrated Circuit(I2C) Overview

SPI allows full duplex / half duplex synchronous serial communication between main and slave ports. There is no explicit communication group frame, error checking, or defined data word length.

Main functions:

1. support up to up to 48MHz
2. support the transmission of 4-32 bit word length
3. at most support, there are four chip selection on each bus (CS).
4. support BAM.

2 SPI Configure Process

2.1 Dts Configure

Adding the new SPI bus is relatively simple. The main modification is DTS file, and the driver system is built without changing it.

Base address

BLSP Hardware ID	QUP core	Physical address
BLSP1	BLSP 1 QUP1	0x78B5000
BLSP1	BLSP 1 QUP2	0x78B6000
BLSP1	BLSP 1 QUP3	0x78B7000
BLSP1	BLSP 1 QUP4	0x78B8000
BLSP2	BLSP 2 QUP1	0x7AF5000
BLSP2	BLSP 2 QUP2	0x7AF6000
BLSP2	BLSP 2 QUP3	0x7AF7000
BLSP2	BLSP 2 QUP4	0x7AF8000

SPI core and QUP core shared base address or correct configuration value.

For example, adding a new SPI 3, first look at the hardware schematic diagram that SPI3_MOSI, SPI3_MISO, SPI3_CLK, SPI3_CS corresponding GPIO for GPIO8, GPIO9, GPIO11, GPIO10 are modified steps as follows:

The documents we have to modify: /kernel/msm-3.18/arch/arm/boot/dts/qcom/sim8950-msm8953.dtsi

```
spi_3: spi@78b7000 { /* BLSP1 QUP3 */
    compatible = "qcom,spi-qup-v2";
    #address-cells = <1>;
    #size-cells = <0>;
    reg-names = "spi_physical", "spi_bam_physical";
    reg = <0x78b7000 0x600>,
        <0x7884000 0x1f000>;
    interrupt-names = "spi_irq", "spi_bam_irq";
    interrupts = <0 97 0>, <0 238 0>;
    spi-max-frequency = <19200000>;
    pinctrl-names = "default", "sleep", "cs_default";
    pinctrl-0 = <&spi3_default &spi3_cs0_active>;
    pinctrl-1 = <&spi3_sleep &spi3_cs0_sleep>;
    clocks = <&clock_gcc clk_gcc_blsp1_ahb_clk>,
        <&clock_gcc clk_gcc_blsp1_qup1_spi_apps_clk>;
    clock-names = "iface_clk", "core_clk";
    qcom,infinite-mode = <0>;
    qcom,use-bam;
    qcom,use-pinctrl;
    qcom,ver-reg-exists;
    qcom,bam-consumer-pipe-index = <8>;
    qcom,bam-producer-pipe-index = <9>;
    qcom,master-id = <86>;
    status = "ok";
};
```

2.2 GPIO SPI Configure

The documents we have to modify :

/kernel/msm-3.18/arch/arm/boot/dts/qcom/sim8950-msm8953-pinctrl.dtsi

```
spi3 {
    spi3_default: spi3_default {
        /* active state */
        mux {
            /* MOSI, MISO, CLK */
            pins = "gpio8", "gpio9", "gpio11";
            function = "blsp_spi3";
        };
        config {
            pins="gpio8", "gpio9", "gpio11";
            drive-strength=<12>;
        };
    };
};
```

```
        bias-disable = <0>;
    };
};
spi3_sleep: spi3_sleep {
    /* suspended state */
    mux {
        /* MOSI, MISO, CLK */
        pins="gpio8", "gpio9", "gpio11";
        function = "gpio";
    };
    config {
        pins="gpio8", "gpio9", "gpio11";
        drive-strength=<2>;
        bias-pull-down;
    };
};

spi3_cs0_active: cs0_active {
    /* CS */
    mux {
        pins= "gpio10";
        function = "gpio";
    };
    config {
        pins="gpio10";
        drive-strength= <2>;
        bias-disable = <0>;
    };
};
};
```