



PCB.LaYoUT

Specifications:  
 Electrical: Contact Resistance  
 30 milliohms MAX  
 Dielectric Withstanding Voltage:  
 500 V AC AT Sea Level  
 Insulation Resistance:  
 1000 MEGA ohms MIN  
 Material: PBT  
 Contact: Copper Alloy C2680H  
 Shell: Copper Alloy C2680H/Spcc

Finish:  
 Contact: Plated Gold in Mating Area;  
 Tin/ On Solder Tails  
 Shell: Nickel Plating

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 参考	TOLERANCE 容許公差 .0 ± 0.30 .00 ± 0.20 ANG. ± 3°	PART NAME 品名 USB B TYPE DIP TYPE 4P FEMALE RIGHT ANGLE HORIZONTAL TYPE NICKEL SHELL SELECTIVE GOLD PLATING ROHS
DWG. 製圖 Betty	UNIT 單位 MM	SIZE 紙張尺寸 A 4	PART NO. 料號 C8317-04BFHSX0R
DATE 制表日 2014/04/25	PAGE 張數 1 OF 1	REV. 版次 B	