



- SPEC :
- 1.Housing:High-Temp Plastic,UL94-V  
Color : Natural
  - 2.Locker:High-Temp Plastic,UL94-V  
Color : Black
  - 3.Contact : Phosphor Bronze  
Initial:30m Ohms Max.  
Voltage Rating:50V AC,DC
  - 4.Solder Tab:BRASS
  - 5.Temperature Rating: -40°C~+85°C
  - 6.Dielectric Withstanding Voltage:500V AC/Min

PIN	DIM.A	DIM.B	DIM.C	DIM.D	PIN	DIM.A	DIM.B	DIM.C	DIM.D
4	6.40	1.50	6.00	2.50	43	25.90	21.00	25.50	22.00
5	6.90	2.00	6.50	3.00	44	26.40	21.50	26.00	22.50
6	7.40	2.50	7.00	3.50	45	26.90	22.00	26.50	23.00
7	7.90	3.00	7.50	4.00	46	27.40	22.50	27.00	23.50
8	8.40	3.50	8.00	4.50	47	27.90	23.00	27.50	24.00
9	8.90	4.00	8.50	5.00	48	28.40	23.50	28.00	24.50
10	9.40	4.50	9.00	5.50	49	28.90	24.00	28.50	25.00
11	9.90	5.00	9.50	6.00	50	29.40	24.50	29.00	25.50
12	10.40	5.50	10.00	6.50	51	29.90	25.00	29.50	26.00
13	10.90	6.00	10.50	7.00	52	30.40	25.50	30.00	26.50
14	11.40	6.50	11.00	7.50	53	30.90	26.00	30.50	27.00
15	11.90	7.00	11.50	8.00	54	31.40	26.50	31.00	27.50
16	12.40	7.50	12.00	8.50	55	31.90	27.00	31.50	28.00
17	12.90	8.00	12.50	9.00	56	32.40	27.50	32.00	28.50
18	13.40	8.50	13.00	9.50	57	32.90	28.00	32.50	29.00
19	13.90	9.00	13.50	10.00	58	33.40	28.50	33.00	29.50
20	14.40	9.50	14.00	10.50	59	33.90	29.00	33.50	30.00
21	14.90	10.00	14.50	11.00	60	34.40	29.50	34.00	30.50
22	15.40	10.50	15.00	11.50	61	34.90	30.00	34.50	31.00
23	15.90	11.00	15.50	12.00	62	35.40	30.50	35.00	31.50
24	16.40	11.50	16.00	12.50	63	35.90	31.00	35.50	32.00
25	16.90	12.00	16.50	13.00	64	36.40	31.50	36.00	32.50
26	17.40	12.50	17.00	13.50	65	36.90	32.00	36.50	33.00
27	17.90	13.00	17.50	14.00	66	37.40	32.50	37.00	33.50
28	18.40	13.50	18.00	14.50	67	37.90	33.00	37.50	34.00
29	18.90	14.00	18.50	15.00	68	38.40	33.50	38.00	34.50
30	19.40	14.50	19.00	15.50	69	38.90	34.00	38.50	35.00
31	19.90	15.00	19.50	16.00	70	39.40	34.50	39.00	35.50
32	20.40	15.50	20.00	16.50	71	39.90	35.00	39.50	36.00
33	20.90	16.00	20.50	17.00	72	40.40	35.50	40.00	36.50
34	21.40	16.50	21.00	17.50	73	40.90	36.00	40.50	37.00
35	21.90	17.00	21.50	18.00	74	41.40	36.50	41.00	37.50
36	22.40	17.50	22.00	18.50	75	41.90	37.00	41.50	38.00
37	22.90	18.00	22.50	19.00	76	42.40	37.50	42.00	38.50
38	23.40	18.50	23.00	19.50	77	42.90	38.00	42.50	39.00
39	23.90	19.00	23.50	20.00	78	43.40	38.50	43.00	39.50
40	24.40	19.50	24.00	20.50	79	43.90	39.00	43.50	40.00
41	24.90	20.00	24.50	21.00	80	44.40	39.50	44.00	40.50
42	25.40	20.50	25.00	21.50					

**RoHS Compliant** **HSM 玄茂科技股份有限公司**  
**HSUAN MAO TECHNOLOGY CO., LTD.**

APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	UNIT 單位	SIZE 線規尺寸	
DATE 制表日	PAGE 張數	REV. 版本	PART NO. 料號

Helen  
2019/2/21  
1 OF 1  
A

FPC/FPC ZIF 0.5mm PIANO TYPE SMT TYPE H=2.0mm  
??PIN BOTTOM CONTACTS REEL PACKING IVORY COLOR ROHS  
C3944-XXBXR100R