



Specifications:

Electrical:

Contact Resistance: 30 milliohms MAX

Dielectric Withstanding Voltage:

500 V AC AT Sea Level

Insulation Resistance: 100 MEGA ohms MIN

Material:

Housing: High Temperature Thermoplastics

Contact: Copper Alloy

Shell: Copper Alloy

Finish:

Contact: Plated Gold in Mating Area;
Tin On Solder Talls

Shell:

Nickel/ Plating

RoHS Compliant		HSM 玄茂科技股份有限公司 HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 HELEN		TOLERANCE X ±0.3 XX ±0.2 XXX ±0.1 XXXX ±0.05	PART NAME 品名 MINI USB(1.1) 5P FEMALE P.C.B. OFFSET TYPE SMT TYPE SELECTIVE GOLD PLASTIC WITHOUT LOCATING PEG BLACK INSULATOR TUBE PACKING ROHS
DWG. 製圖 ABBY	SCALE 比例 參 考	UNIT 單位 M M	PART NO. 料 號 C8352-05BFDXBTR
DATE 制表日 2011/04/19	PAGE 張數 1 OF 1	SIZE 紙張尺寸 A 4	REV. 版本 A