






REV	CONTENT	CHK	DATE
V0.0	CONTENT	ZCL	24.06.18



RAILWAY ASSEMBLY MAP



PCB LAYOUT
PCB THICKNESS :1.4-1.7mm

Electrical :

- 1.Rated Voltage : 150V
- 2.Rated Current : 7A
- 3.Operating Temperature : -40°C~+105°C
- 4.RoHS Compliance
- 5."★" is the key quality control point

GTKTUS - 3.81 -XXP - X X - 10

① ② ③ ④ ⑤ ⑥

- ① Series NO.
- ② Pitch
- ③ Poles
- ④ 1 Single Pitch
2 Double Pitch
- ⑤ Color: 1 Grey
2 Blue
3 Black
4 Green
5 Orange
6 Red
7 Transparent
8 Yellow
9 White
- ⑥ Customer Request: 10--Customized

3	PIN	XX	5	Copper alloy	Au0.8-1.4um Plated
2	Cover	XX	1	PA66	UL94V-0
1	Housing	XX	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	ZCL	DATE	24.06.18	SIZE	A4 UNITS mm SHEET/OF 1/1
CHK.		DATE		SCALE	1:1
APP.		DATE		NAME	GTKTUS-3.81-XXP-XX-10
				DWGNO.	XXXX

Golten 宁波冠泰电子有限公司
NINGBO GOLTEN ELECTRONICS CO., LTD.

A	Total Pitch Tolerances in mm									Nominal dimension range in mm									$\perp$		$\equiv$	$—$		$//$	
	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 320	over 0	over 10	all	over 0	over 100	over 150
	to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10	to 10		to 0	to 100	to 150	
	± 0.18	± 0.20	± 0.25	± 0.3	± 0.35	± 0.44	± 0.60	± 0.70	± 0.85	± 0.20	± 0.25	± 0.30	± 0.35	± 0.44	± 0.55	± 0.70	± 0.80	± 0.90	0.2	0.3	0.3	0.2	0.3	0.5	